HIPPOTIZER

AMBA

With the capacity for an internal capture card and a removable drive; the Hippotizer Amba outperforms many larger systems.

With a single unlimited resolution output, the Hippotizer Amba can be used with splitters or on greater than HD projects.

YOUR DEDICATED HARDWARE

Output Specifications	AMBA DP
Production Video Outputs	1
Production Output Connector	1 x DP 1.2
Max Resolution per DP output	4096 x 2160
Video Splitter Support	Yes
Additional Control outputs (ZK)	2x DVI, 1x DP 1.2
Genlock	No

Software Specs	
Max mixes	4
Layers per Mix	16
4K playback*	upto 2
HD playback*	upto 8
Software Update Period****	3 Years

Hardware Specs	
Video Capture*****	Yes: 1 Card
Media Storage	500GB Solid State
Media Storage Speed	400 MB/s
HippoNet Network	1Gb Cat 5
Data Network	1Gb Cat 5
Audio Input Connections	3.5mm Stereo
Audio Output Connections	3.5mm Stereo
MultiChannel Audio Support	Via USB
Hardware EDID Management	
Software EDID Management	Yes

Optional Touch Screen	
Optional Redundant PSU	
SMPTE Timecode In	Optional

ACCESSORIES
STRATA Caddy Drive 480Gb
STRATA Caddy Drive 900Gb
Extra power lead
Additional Input Card Cables
10GB HippoNet upgrade
Flight Case

Input cards
2 x DVI Input card
2 x HD-SDI Input card
2 x Displayport 1.2 Input card
1 x DVI-HDSDI Input card
4 x HD-SDI Input card
SMPTE IN card

* For reference only. Tested with 30FPS FlexRes Performance Codec. Numbers of Layers, Mixes, Viewports, and other processing (such as SHAPE) may result in less
** Number of Outputs to use at once software limited
*** Maximum resolutions at 60Hz. Higher resolutions may be possible at lower frame rates
**** Time from date of purchase or 1/10/15; whichever is later where updates to new Hippotizer V4 software is free of charge.
***** Specify at time of purchase.

HEAD OFFICE 307 PARMA HOUSE, CLARENDON ROAD, LONDON, N22 6UL, UNITED KINGDOM 0203 30 4561 | SALES@GREEN-HIPPO.COM
US OFFICE 425 EAST COLORADO STREET, GLENDALE, CA, 91505, USA. 818 239 4778 | USSALES@GREEN-HIPPO.COM