EXPANSION MODULE SPEC

HDMI-2K4IN

OVERVIEW

This module adds four HDMI 1.4 inputs, supporting up to 1080p (1920x1080) 60Hz	
Features	
HDMI 1.4	1080p (1920x1080) 60Hz
HDCP 1.4	Yes
Designed For	
ESTUARY MC models with input expansion slots	Input expansion module for ESTUARY models
Max Installable	
ESTUARY - MC2	1 module
ESTUARY - MC4	8 modules
Installation	
Field upgradable expansion module	Can be fitted in to slots 11 or 12 in ESTUARY MC2 model (only fit in to slot 12 if you plan to leave slot 11 empty or only add the audio breakout module)
Caution	This is not a hot-swappable item. To install or replace the unit has to be powered down and disconnected from the supply. Observe static safety precautions when handling the module. Must be installed by a competent person

VIDEO INPUTS

HDMI	4x
HDCP	1.4
Chroma sub-sampling	4:4:4
Color depth	8-bit
Color space	SDR YUV (L) BT.601, SDR YUV (L) BT.709, SDR RGB (L) BT.709, SDR RGB (F) BT.709 and auto detect

SUPPORTED INPUT RESOLUTIONS

480i (720x480)	59.94Hz
480p (640x480)	60, 72, 75, 85Hz
480p (720x480)	59.94Hz
487i (720x487)	59.94Hz
576i (720x576)	50Hz
576p (720x576)	50Hz
600p (800x600)	56, 60, 72, 75, 85Hz
720p (1280x720)	29.97, 30, 50, 59.94, 60Hz
720p (1920x720)	60Hz
768p (1024x768)	60, 70, 75, 85Hz
768p (1280x768)	60, 75, 85Hz
768p (1360x768)	60Hz
800p (1280x800)	60, 75, 85Hz
864p (1152x864)	70, 75Hz
900p (1400x900)	60Hz
900p (1440x900)	60, 75, 85Hz
900p (1600x900)	60Hz
960p (1280x960)	60, 85Hz
980p (980x980)	75Hz
1024p (1280x1024)	50, 60, 75, 85Hz
1050p (1400x1050)	50, 60, 75Hz
1050p (1680x1050)	60Hz
1080i (1920x1080)	50, 59.94, 60Hz
1080p (1920x1080)	23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz

EXPANSION MODULE SPEC

HDMI-2K4IN

AUDIO	
Supported sampling rate	48kHz
Sample size	24 bits
Supported channels	One stereo pair per input
WARRANTY	
Limited warranty	2 years parts and labor (must be installed by a competent person)
Regulatory Compliance	
System / modules	FCC, CE, RoHS, UL, UKCA
ENVIRONMENTAL	
Operating temperature	32° to 104°F (0° to +40°C)
Operating humidity	10% to 85%, Non-condensing
Storage temperature	14° to +158°F (-10° to +70°C)
Storage humidity	10% to 85%, Non-condensing
POWER	
Powered by the ESTUARY main unit	